

Range: DS

Double skin glass and dishwashers DS line.

Designed to meet the needs of bars, restaurants, hotels and pubs.

Their aesthetics has recently been renewed; electromechanical and electronic versions are now available.

A wide choice of options may be chosen amongst water softener, detergent dispenser, drain pump and the new surface filters in order to adapt the machine to the most diverse uses.



FEATURES

- Double skin AISI 304 structure
- Deep-formed rack supports
- Door with anti-shock system
- Deep-drawn and sloped tank for a perfect total drain
- Non-drip roof to safeguard the hygiene of the freshly washed dishes
- Overflow and drain pipes integrated system for a triple protection of the wash pump
- Light wash and rinse arms granting the best efficiency also in the event of weak pressure in the water mains
- Easy to remove nozzles to help with daily cleaning operations
- Electronic version with 4 preset wash cycles
- Self-cleaning cycle
- Soft Start wash pump that offers additional protection for the most delicate objects
- Non-return valve to prevent the water backflow
- Thermostop system: the rinse starts only when the water in boiler reaches 85 °C
- Rinse aid dispenser

OPTIONS

- Special voltages
- Drain pump
- Built-in peristaltic detergent dispenser
- Peristaltic rinse aid dispenser
- Final rinse with cold water
- Round basket
- Built-in water softener with automatic regeneration

Option compatibility to be confirmed by the manufacturer after verification

CAPACITY






305 H Ø 295 400x400

RACK EQUIPMENT

- 2 X C121
- 1 X 10728
- 1 X 15060



DOUBLE SKIN GLASS & DISHWASHERS



TECHNICAL FEATURES

EXTERNAL DIMENSIONS

Width	mm	460
Depth	mm	545
Height (screwed foot)	mm	715
Weight (standard version)	kg	38

TECHNICAL DATA

Basket dimensions	mm	400x400
Glasses maximum useful height	mm	305
Maximum dish diameter	mm	295
Maximum level of water discharge	mm	40
Water inlet temperature	°C	55
Maximum inlet water hardness	°f	8
Inlet water pressure	kPa	200 - 400
Tank capacity	l	15.5
Tank heating element	kW	1.25
Boiler capacity	l	3.4
Boiler heating element	kW	2.8
Wash pump power	kW	0.4
Wash pump flow rate	l/min	185
Sound pressure level	dB(A)	< 70

POWER SUPPLY DATA

Supply voltage		220-240 V 50 Hz
Total installed power	kW	3.2

DOUBLE SKIN GLASS & DISHWASHERS

CYCLES					
Cycle number		1	2	3	4
Cycle length	s	60	90	120	180
Cycle productivity (racks/h) - 55°C inlet water		60	40	30	20
Cycle productivity (racks/h) - 10°C inlet water		16	16	16	16
Cycle water consumption	l	1.8	1.8	1.8	1.8
Rinsing temperature setting	°C	85	85	85	85
Washing temperature setting	°C	55	55	55	55

Standard Thermostop. In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.